

Quietstep / 5

- Heterogeneous vinyl sheet
- Available marbled grey, solid black, and grey

SPECIFICATION



3.0mm
.12 in



2.0mm
.08 in



Quietstep
2m x 20m (6.56ft x 65ft)
Quietstep 5
1.5m x 20m (5ft x 65ft)



3.26kg/m²
6.0lbs/yd²

HOMOGENOUS
FOAM BACKED

QUIETSTEP / 5

HOMOGENOUS
FOAM BACKED

PERFORMANCE AND
PROPERTIES



GENERAL PERFORMANCE
EN 651



**ACOUSTIC IMPACT SOUND
REDUCTION**
EN ISO 140-8 ≥ 19 dB



SLIP RESISTANCE
EN 13893 Class DS (dry condition)
DIN 51130 R9



REACTION TO FIRE
EN 13501-1 Class Bfl-S1
EN ISO 9239-1 (5) ≥ 8.0 kW/m²
EN ISO 11925-2 (B) F_s ≤ 150 mm within 20s



RESISTANCE TO CHEMICALS
EN 423 (ASTM F 1303-99)
Excellent chemical resistance



LIGHT FASTNESS
EN 20105-B02 (Method 3) ≥ 6



ABRASION RESISTANCE
EN 649 Group T



INDENTATION - RESIDUAL
EN 433 < 0.2 mm



DIMENSIONAL STABILITY
EN 434 $< 0.10\%$



FLEXIBILITY
EN 435 (Method A) Pass
20mm \emptyset



VOC EMISSIONS
ENV 13419 AgBB VOC test: Pass
(Low Result)



THERMAL CONDUCTIVITY
Suitable for use with underfloor
heating Max 27°C



HYGIENE
Contains antimicrobial agents for improved hygiene protection.
This product has been independently tested and results demonstrate that it
inhibits the growth of MRSA. An effective cleaning regime is however, the most
important defence against infection.



ELECTRICAL BEHAVIOUR (body voltage)
EN1815 This product does not accumulate static charges above 2kV and is
classified as 'antistatic'.



APPLICATIONS
*When used with a sprung subfloor Quietstep / 5 is an ideal ballet, modern
pointe dance surface. It can also be used for touring, theater, and light
aerobic exercise*



For information regarding handling and installation, adhesives, maintenance,
applications and chemical resistance,
call 800-523-0960

Stagestep Inc. 4701 Bath St #46, Philadelphia Pa 19137
215-636-9000 - 800-523-0960
www.stagestep.com