






RAVE

- Hardwearing, heterogenous reversible sheet flooring
- Colors - Black, Grey, White, Tan


















SPECIFICATION

 2.0mm .08 in	 N/A
 N/A	 2m x up to 20m 6.56ft x up to 65ft
	 1.90kg/m2 3.5 lbs/yd2

RAVE

HETEROGENOUS

PERFORMANCE AND PROPERTIES

 GENERAL PERFORMANCE EN 651	
 ACOUSTIC IMPACT SOUND REDUCTION ISO 717-2 19dB	 SLIP RESISTANCE AS/NZS 4856 R9 DIN 51130 R9
 REACTION TO FIRE EN 13501-1 Class Cfl-s1	
 RESISTANCE TO CHEMICALS EN 423 (ASTM F 1303-99) Excellent chemical resistance	 LIGHT FASTNESS EN 20105-B02 (Method 3) ≥6
 ABRASION RESISTANCE EN 649 Group T	 INDENTATION - RESIDUAL EN 433 <0.2mm
 DIMENSIONAL STABILITY EN 434 0.2	 FLEXIBILITY EN 435 (Method A) Pass
 VOC EMISSIONS No Solvents Used	 THERMAL CONDUCTIVITY N/A
 HYGIENE Contains antimicrobial agents for improved hygiene protection. This product has been independently tested and results demonstrate that it inhibits the growth of MRSA. An effective cleaning regime is however, the most important defence against infection.	
 ELECTRICAL BEHAVIOUR (body voltage) EN1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'.	
 APPLICATIONS Ballet, Modern, Jazz, Call for percussive use	
 For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, call 800-523-0960	

