

ENCORE ELITE – MAPLE - 12622010

Encore Elite is 3-strip engineered wood floor with silk matte finish, cleaner graining and color variation than Hard Maple Manitoba. Underlayment a combination of layers of plywood and closed cell, closed linked, polyethylene, EVA foam. The floor can be sanded by a professional 2-3 times.

PANEL LENGTH:	95.25" (2.42 lm)
PANEL WIDTH:	7.875" (200 mm)
PANEL AREA:	5.22 sf (0.485 m2)
PANEL THICKNESS:	1.375" (34.9 mm)
PANEL WEIGHT:	11.5 lbs (5.2 kg)
WEAR LAYER THICKNESS:	.14" (3.5 mm)
HARDNESS (Brinell Value):	3.2 – 6.9
INSTALLATION:	Click & Lock (Woodloc® 5S), Stagger, Perimeter Gap
RESIDUAL INDENTATION:	Specified Load 250 psi Residual Compression .001 inch ASTM 970
FORCE REDUCTION:	45.6% Class 5 ASTM F2569 ASTM F2772
VERTICAL DEFORMATION:	3.0 mm Passes ASTM F2772
ROLLING LOAD:	150 lbs per wheel 500 cycles .004 inch ASTM F2753 (2670 N total force)

Stagestep, 4701 Bath St, Bldg 46B, Philadelphia, PA 19137



a company of The Gerflor logo, consisting of the word "Gerflor" in a bold, blue, sans-serif font with a registered trademark symbol, positioned to the right of the text "a company of".